

Aquilon RS alpha

Ref. AQL-RS-ALPHA



Mission-critical 4K/8K multi-screen presentation system and videowall processor with 8 inputs and 4 outputs, delivering uncompromising presentation experiences to high-end staging and premium system integration



Outstanding Performances

Like its larger siblings of the **LivePremier™** series, **Aquilon RS alpha** offers versatile 4K digital connectivity, unmatched real-time 10/12-bit 4:4:4 video processing power, best-in-class image quality and pure 4K60p on each input and output with ultra-low latency. Ideally tailored to large scale auditoriums, conference rooms, staging live events, houses of worships, corporate lobbies and sports venues, **Aquilon RS alpha** offers almost unlimited possibilities for future applications and possesses enough bandwidth to support evolving requirements, such as 8K and higher framerates.

Industrial Grade Reliability

Aquilon RS alpha was specifically engineered to perform to the highest standards in mission-critical applications and road-hardened to survive frequent shipping and tough live events. By combining a heavy-duty modular design, the highest quality components selected for their proven reliability, and features such as redundant swappable power supplies and smart thermal management, **Aquilon RS alpha** delivers uninterrupted 24/7 performance and peace of mind!

Versatile for the Highest Flexibility of Configurations

Aquilon RS alpha's modular design allows you to easily swap I/O cards to accommodate a variety of connectivity arrangements and your match source and display requirements. **Aquilon RS alpha** offers 8 seamless inputs, 4 outputs configurable as single screens, edge-blended widescreens or scaled auxiliary outputs, 2 dedicated Multiviewer outputs, up to 4x 4K or 8x HD freely assignable mixing layers, as well as powerful features that will allow you to handle any creative display configuration, such as a custom output formats, output rotation, AOI, bezel compensation and pixel pitch management.

Smart Functionalities

Aquilon RS alpha features state-of-the-art real time processing features that will help you to unleash all your creative potential and produce flawless, stunning shows: true seamless switching, real-time SDR/HDR conversion, flying layer movement, advanced cut and fill, cutting edge keying engine... **Aquilon RS alpha** also allows to remove external audio de-embedding boxes: In just a few easy clicks, audio can be de-embedded from video sources, routed directly using onboard Dante™ card and re-embedded from external audio processor for sending to display, recording device, or streaming.

8
inputs

4
outputs

4K60
4:4:4
10-12 bit

2
multi-
viewers

HDR

Dante

HDMI
2.0

HDCP
2.2

Aquilon RS alpha at a glance

- ▶ Industrial grade reliability
- ▶ 8x HDMI 2.0 inputs and 4x HDMI 2.0 outputs (field swappable I/O cards)
- ▶ I/O cards available separately: DP, SDI, HDMI, SFP+ and Fiber Optical
- ▶ True 4K60p 4:4:4 performance on every I/O channel
- ▶ Ultra-low latency 10/12-bit 4:4:4 video processing
- ▶ 40 Megapixels throughput on Program at 10-bit 4:4:4 @60Hz
- ▶ Up to 4x 4K or 8x DL/2K mixing layers (+live backgrounds)
- ▶ Real-time SDR/HDR10/HLG conversion
- ▶ Intuitive HTML5-based user interface with live source thumbnails
- ▶ Native DANTE audio networking hardware and support
- ▶ Future proof modular design

Aquilon Models	RS alpha	RS1	RS2	RS3	RS4	C	C+
4K60p inputs	8	16	16	24	24	up to 16	up to 24
4K60p outputs	4	8	12	12	16	up to 16	up to 20
Max 4K mixing layers*	4	4	8	8	12	up to 8	up to 12
Max DL/2K mixing layers*	8	8	16	16	24	up to 16	up to 24
Simul. 4K still image channels	12	12	12	24	24	up to 12	up to 24
Build-to-Order (BTO)						✓	✓
Rack units	4	4	4	5	5	4	5

* doubled for split layers


Key Features

- Based on LivePremier™ platform
- Highly ruggedized chassis with cleanable air filter
- Swappable redundant power supplies (1+1)
- 8x seamless 4K60p HDMI 2.0 inputs
- 4x 4K60p HDMI 2.0 active outputs
- True 4K60p 4:4:4 performance on every I/O channel
- Ultra-low latency 10 and 12-bit processing
- Full set of field swappable I/O cards available separately (DP 1.2, 12G-SDI, HDMI 2.0, SFP+, Optical) to accommodate any connectivity arrangements
- Support 4K60p input and output as single, double or quad plugs
- Compatible with Analog Way DPH104 video processor: easily convert one 4K DP 1.2 output to 4 independent full HD outputs (requires a DP output card)
- 40 Megapixels throughput at 10-bit 4:4:4 on Program, without restricting Preview or Multiviewer
- Up to 4x 4K or 8x DL/2K mixing layers per system (8x 4K or 16x DL/2K split layers), depending on the screens setup
- 12x 4K or 24x 2K concurrent still images
- Unscaled seamless background mixer on each output (using instantaneous still images or live sources)
- Flexible layer management
- Seamless crossfade on all mixing layers, on all 8 sources
- Scaled 4K60p AUX feature for all non-PGM outputs
- Ability to create layers on AUX outputs without using processing resources
- Ability to place the outputs anywhere on an almost limitless video canvas space for special LED wall applications
- Inboard clocks, timers and countdowns for your screens or AUX outputs

- 2x configurable 4K Multiviewers with 64x resizable widgets
- Advanced pixel pitch management for LED wall applications
- Native Dante™ audio networking hardware and support (64x64)
- Real-time SDR/HDR10/HLG conversion based on 3D-LUTs (BBC)
- Rotation capability on each output (increment of 90°)
- Independent output rates
- Framelock or internal sync. generator
- Web RCS: highly intuitive, lightning fast web-based user interface based on HTML5 with password protection
- Live video thumbnails shown on GUI
- Multi operator real-time collaboration
- Easily create and recall preset looks on all your screens and auxiliary outputs
- Custom output formats for non-standard display applications
- Area of Interest feature to customize active areas of outputs
- Still images support variable alpha-channels for transparent background on logos
- Cut and Fill
- Fully functional simulator for offline configuration and practice
- EDID management on every input and output
- Compatible with HDCP 1.4 and HDCP 2.2
- Future proof modular design
- Quiet: 49dB average noise at 1m
- Remote services and maintenance
- Backup and restore functions

Unrivalled Ease of Use


For the best ease of setup and to ensure flawless control of multi-screen presentations, **Aquilon RS alpha** features a totally new, cutting-edge HTML5-based user interface, the **Web RCS**, compatible with any device or platform including iOS and Android devices. Conceived to greatly increase productivity and reduce learning curve, the **Web RCS** offers dozens of unique features that simplify configuring and operating, such as live resizable program/preview workspaces with high-resolution dynamic thumbnails of connected sources, multi-operator collaboration with password protection, keyword search and much more...




Powerful and Flexible Control Options

In addition to the powerful Web RCS, **Aquilon RS alpha** features IP (Ethernet) control via a standard TCP/IP socket connection supported by all major third-party control systems. It can also be controlled by the free Crestron® driver as well as by **AW VideoCompositor**, a unique solution that gives system integrators and Crestron® developers all the tools they need to easily incorporate the power of LivePremier™ image processors video compositing into a single point of control Crestron® touch-screen application. Additionally, **Aquilon RS alpha** can be controlled by a comprehensive range of remote control solutions from the **Shot Box²** and the **Control Box²** to the powerful standalone event controller, the **RC400T**, featuring premium buttons with dynamic LCD labels, a T-Bar and a Joystick, that will streamline your control of the LivePremier™ series...

Aquilon RS alpha can drive a widescreen with 4x 2K60p outputs and up to four 4K PIPs



Aquilon RS alpha can drive one 8K60p LED wall with up to four 4K PIPs



Technical Specifications

INPUTS

8 seamless 4K60p HDMI 2.0 inputs via 2 field swappable input cards (up to 4K60p 8-bit 4:4:4 or up to 4K60p 12-bit 4:2:2 or up to 4K30p 12-bit 4:4:4)
Input cards available separately: DP, SDI, HDMI, SFP and Fiber Optical
Support 4K60p input as single, double or quad plugs (incl. 4x 3G-SDI 2SI)
Support custom input formats such as "8k x 1k" on a single connector
Connector status LEDs for easy troubleshooting

OUTPUTS

4 active 4K60p HDMI 2.0 outputs via 1 field swappable output card (up to 4K60p 8-bit 4:4:4 or up to 4K60p 12-bit 4:2:2 or up to 4K30p 12-bit 4:4:4)
Output cards available separately: DP, SDI, HDMI, SFP and Fiber Optical
Support 4K60p output as single, double or quad plugs
Support custom output formats such as "8k x 1k" on a single connector
Connector status LEDs for easy troubleshooting

MULTIVIEWER OUTPUTS

2 dedicated HDMI 2.0 outputs configurable as up to 2x 4K30p or up to 2x 2560x1440@60p or 1x 4K60p
64 resizable widgets on each output
Customizable layouts with 50 memories
Monitor inputs, still images, screens (Program and Preview) as well as inboard clocks/countdown/timers

LAYERS & BACKGROUND

Supports mixing layers (true seamless transitions) and split layers (cut transitions)
Up to 4x 4K or 8x Dual/2K mixing layers per system (8x 4K or 16x Dual/2K split layers), depending on the screens setup
Layer source can be a live input, a still image, a screen (for split layers only) or any of the inboard clocks, countdown and timers
Each output has an unscaled background mixer supporting seamless transitions - background source can be still image or live source

SCREENS

Outputs configurable as single screens or edge-blended widescreens
Up to 4x 4K60p program outputs
Ability to place the outputs anywhere on an almost limitless video canvas space for special LED wall applications
Flexible layer management: each screen gets dedicated layers of various sizes (2K, 4K, ...) using common-pool layer resources
1000 screen memories, 50 layer memories and 500 master memories

SCALED AUX OUTPUTS

Any unused output configurable as a scaled auxiliary output
Up to 4x 4K60p scaled auxiliary outputs
Can display any input, screen (1:1 or scaled) or inboard clocks, timers and countdowns
Ability to create resizable layers on AUX outputs without using processing resources (adjacent outputs can be used to increase the layer count)

AUDIO

Audio de-embedding/embedding on every input & output (raw audio)
De-embed audio from sources and route directly to Dante™ network
Re-embed audio from external audio processor for sending to display
64x64 Dante™ channels @48 kHz or 32x32 Dante™ channels @96 kHz
Dual redundancy Ethernet ports - AES67 support

PROCESSING

Based on Analog Way exclusive 5th generation scaling engine
Extremely low latency, as low as 1 frame in proper configuration
BT.601; BT.709; BT.2020 color spaces
Advanced pixel pitch management & bezel compensation
Real-time SDR/HDR10/HLG conversion based on 3D-LUTs
Compatible with HDCP 1.4 and HDCP 2.2
Compatible with Analog Way DPH104 video processor

TRANSITIONS & EFFECTS

True A/B Mix
Misc. layer border effects/colors and separate shadow
Transitions: Cut, Fade, Slide, Wipe, Circle, Stretch, Depth, Flying layer movement with programmable paths
Layer effects: Background Cut, Transparency, Luma/Chroma Key, DSK, H&V Flip, Cut and Fill
Colors effects: B&W, Negative, Sepia and Solarize

STILL IMAGES

12x 4K or 24x 2K concurrent still images - fully resizable
Still images support alpha-channel
Still image library with 100 memories
Multi-file download/upload via Web RCS
Capture from live inputs (beg. 2021)

CONTROL

Web RCS: On-board intuitive web-based user interface
Shot Box²/Control Box²: Cost effective control solutions
RC400T: Ergonomic event controller
Simple REST API (HTTP) and advanced TCP protocol based on JSON
Crestron driver & AW VideoCompositor (Premium Crestron® GUI)

OTHER FEATURES

Tally/GPI-O - EDID management on every input and output
Dedicated BNC with loop out for Framelock, blackburst and tri-level sync
Fully functional simulator for offline configuration & practice

EXPANDABILITY

Expansion via simple linking possible (future hardware upgrade)

Dimension (in Rack Units - RU)

▶ 4RU

Dimensions (without rack ears & rack mount)

▶ W 17.28" x H 6.97" x D 27.56"
▶ L 439.8 mm x H 177 mm x P 700 mm

Dimensions (with handles)

▶ W 18.89" x H 6.97" x D 27.59"
▶ L 482.4 mm x H 177 mm x P 701 mm

Weight without accessories

▶ 23.9 kg / 52.69 lbs

Shipping weight (accessories included)

▶ 42.9 kg / 94.57 lbs

Operating conditions

▶ Temperature: 0 to 40°C (32 to 104°F)
▶ Humidity: 10% to 80%, non-condensing

Noise (@1,6m height @25°C)

▶ Front: 49 DBa@1m
▶ Rear: 51 DBa@1m

Thermal dissipation

▶ 1365 BTU/hr

Warranty

▶ 3-year warranty on parts and labor back to factory excluding I/O connector cards which are warranted for 1 year
▶ Broken connectors are not covered by warranty

Power Supply

▶ 100-240 VAC, 12-7A 50/60Hz
▶ Swappable redundant power supplies (1+1)
▶ Max consumption: 400 W

Safety Compliance

▶ IEC/UL/EN 62368-1, CSA22.2 #62368-1

EMC & Environmental Compliance

▶ EN55032, EB55024, EN61000, FCC part15, ICES

Supplied with

▶ 2x Power supply cords
▶ 1x Web-based Remote Control Software
▶ 1x Rackmount kit
▶ 1x Ethernet cross cable
▶ 3x MCO 5 pin connectors
▶ 1x User manual (PDF)
▶ 1x Quick start guide + safety instructions

 Specifications subject to change without prior notice AQL-RS- ALPHA_EN-01/22/2021