

ClickShare CX-20

Transform small meeting rooms and huddle spaces into inspiring conference facilities.



- Full BYOD support
- Remote collaboration
- Triple agnostic: works with any device, and UC technology and any brand of AV peripheral
- Enhanced security
- Connected and cloud managed
- Delivered with 1 Conferencing Button
- Collaborate with Conferencing Button or Collaboration App

The modern world of enterprise requires smooth collaboration and flexibility, especially when it comes to team meetings in huddle rooms, and this is exactly what Barco ClickShare CX-20 provides. Encouraging creative innovation through seamless wireless conferencing, ClickShare CX-20 can make meetings more inspiring and more productive.

Announced now, available soon
Start a huddle meeting from your device
Decide how you want to collaborate
Enhanced security and seamless integration

TECHNISCHE DATEN**CLICKSHARE CX-20**

Abmessungen ClickShare-Grundgerät	
Abmessungen (HxBxT)	34 mm x 135 mm x 135 mm
Stromversorgung	Standard 110/220 V AC plug
Stromverbrauch	Operational: 5-10W, 24W Max
Gewicht	900 gr
Allgemeine technische Daten	
Betriebssystem	Windows 8/8.1/10, macOS 10.13 and higher. Android v9 and higher (ClickShare app). iOS 12 and higher (ClickShare app)
Video-Ausgänge	4K UHD (3840*2160) @ 30Hz, HDMI 1.4b
Audioausgang	USB, HDMI
USB	1 X USB-A, 1 X USB-C
Clickshare Buttons	1
ClickShare App	Desktop & Mobile
Native protocols	Aiplay, Google Cast, Miracast*
Geräuschpegel	Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C
Authentifizierungsprotokoll	WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode
Drahtloses Übertragungsprotokoll	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Reichweite	Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHz and 5 GHz (DFS)
Frequenzband	2.4 GHz and 5 GHz (DFS channels supported in select number of countries)
Verbindungen	1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front)
Temperaturbereich	Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)
Luftfeuchtigkeit	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing
Diebstahlschutz	Kensington lock
Zertifizierungen	FCC/CE
Touch screen support & Interactivity	/
Room Dock (peripheral support)	Yes
Local view & moderation	Local view of the room display only
Netzwerk-Verbindung	LAN & WiFi *
Management and reporting	Yes
Gewährleistung	1 year standard, 5 years coverage via SmartCare
*	* depends on configuration, available in future firmware updates

Generiert am: 27 Jan 2020

Die angegebenen Informationen und Daten sind typisch für das beschriebene Gerät. Jede Spezifikation kann sich aber ohne vorherige Ankündigung ändern. Die aktuelle Version dieser Broschüre finden Sie unter www.barco.com.