

In-Wall System Controller Accessories

CB-8



The CB-8 is an installation accessory designed to provide convenient and reliable connections for up to eight RTI in-wall touchpanels. Multiple CB-8's may be daisy-chained to accommodate more than four in-wall devices. In addition to providing power, the CB-8 combines and routes the infrared outputs from the touchpanels to a single output for connection to an RTI controller.

Key Features

- Includes 16 VDC/4,3 A power supply capable of powering up to four RTI in-wall touchpanels
- Combines and routes the infrared output from in-wall system controllers to a single output for connection to an RTI control processor
- Dual power sense inputs are provided for sharing status feedback to all of the touchpanels
- Multiple CB-8 units can be daisy-chained for connecting more than eight in-wall touchpanels
- RJ45 ports and screw down terminals

Specifications

Power	16 VDC / 4,3 A
Maximum Current per Port	1,5 A
PWR/AUX Status Input Voltage	.5 – 16 VDC
Enclosure	Formed steel, black powder coating
Dimensions (W x H x D)	239 x 127 x 2,54 mm
Mounting	Wall-mount or free standing
Weight	700 g
Warranty	One Year (Parts & Labor)
Scope of Delivery	CB-8, power supply, CAT5 cable

PS16-1



The PS16-1 is used to power a single in-wall touchpanel, when a CB-4 connecting block is not used.

Specifications

Power Supplied	16 VDC, 1,6 A, 25 W
Dimensions (W x L x H)	94 x 56 x 34 mm
Weight	290 g
Warranty	One Year (Parts & Labor)